


Recessed Lights

● Plug&Play System



500mA Lumen Output 3000K	9W 500mA - 750 lm
14° Lens	7Q4550. _ _ _ _
18° Lens	784550. _ _ _ _
24° Lens	7G4550. _ _ _ _
33° Lens	7E4550. _ _ _ _
52° Lens	754550. _ _ _ _

24V Lumen Output 3000K	9,5W 24Vdc - 750 lm
14° Lens	7Q4679. _ _ _ _
18° Lens	784679. _ _ _ _
24° Lens	7G4679. _ _ _ _
33° Lens	7E4679. _ _ _ _
52° Lens	754679. _ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● 4 Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● 3 Gray	● B2 2400K CRI > 90	● 1 Gold Chrome	E Elliptical Filter
● 6 Stainless Steel AISI 316L	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
	● 6 3000K	● N Satin Nickel	P Prismatic Filter
	● W 3000K CRI > 90	● 1 Shiny Chrome	S Softening Lens
	● K 3500K CRI > 90		
	● D 4000K CRI > 90		




SUGGESTED DRIVERS (not included)

500mA	CC14-F-500-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708


ACCESSORIES



INTERCHANGEABLE ACCESSORIES p. 676



Aluminum recessed box A01416.40



Watertight connector p. 682 A00387.40

EXAMPLE CODE COMPOSITION

