


Recessed Lights



[1] 14° Lens not interchangeable

IP67 WIPS 500 24V 1 m 400 g 2 2,6



	500mA Lumen Output 3000K	9W 500mA - 750 lm
14° Lens [1]	7Q4549	__ _ _ _
18° Lens	784549	__ _ _ _
24° Lens	7G4549	__ _ _ _
33° Lens	7E4549	__ _ _ _
52° Lens	754549	__ _ _ _

	24V Lumen Output 3000K	9,5W 24Vdc - 750 lm
14° Lens [1]	7Q4678	__ _ _ _
18° Lens	784678	__ _ _ _
24° Lens	7G4678	__ _ _ _
33° Lens	7E4678	__ _ _ _
52° Lens	754678	__ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
4 Black	U1 2200K CRI > 90	4 Black	W Without Filter
3 Gray	B2 2400K CRI > 90	I Gold Chrome	E Elliptical Filter
6 Stainless Steel AISI 316L	X 2700K CRI > 90	8 Satin Gold	H Hex Louver
	6 3000K	N Satin Nickel	P Prismatic Filter
	W 3000K CRI > 90	1 Shiny Chrome	S Softening Lens
	K 3500K CRI > 90		
	D 4000K CRI > 90		




SUGGESTED DRIVERS (not included)

500mA	CC14-F-500-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708


ACCESSORIES



INTERCHANGEABLE ACCESSORIES
p. 676



Aluminum recessed box
A01416.40



Watertight connector p. 682
A00387.40

EXAMPLE CODE COMPOSITION

