Ariel PN-F

Projectors



[1] 14° Lens not interchangeable


FIXING FRAME



MODULE



IP40	250 500 600	280 g	Ø51	2	2,5



Ariel PN-F fixing frame

FIXING FRAME	A01726.30

Ariel PN-F module

500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens [1]	7Q4817._ _ _ _	7Q4999._ _ _ _
18° Lens	784817._ _ _ _	784999._ _ _ _
24° Lens	7G4817._ _ _ _	7G4999._ _ _ _
33° Lens	7E4817._ _ _ _	7E4999._ _ _ _
52° Lens	754817._ _ _ _	754999._ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
H Black	U1 2200K CRI > 90	4 Black	W Without Filter
M8 Brown	B2 2400K CRI > 90	8 Satin Gold	E Elliptical Filter
G3 Gray	X 2700K CRI > 90	I Gold Chrome	H Hex Louver
C Gothic Cement	X1 2700K CRI > 95	N Satin Nickel	P Prismatic Filter
G7 Beige Gray	6 3000K	1 Shiny Chrome	S Softening Lens
A6 Gray White	W 3000K CRI > 90		
S Warm White	W1 3000K CRI > 95		
7 White	K 3500K CRI > 90		
	K1 3500K CRI > 95		
	D 4000K CRI > 90		

Ariel PN-F dynamic white module

250mA Lumen Output 3000K CRI > 90	9W 250mA - 670 lm
33° Lens	7E4974._ _ _ _
52° Lens	754974._ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
H Black	T DIM TO WARM 1800K / 3000K CRI > 90	4 Black	W Without Filter
M8 Brown	M2 TUNABLE WHITE 1800K / 4000K CRI > 90	8 Satin Gold	E Elliptical Filter
G3 Gray		I Gold Chrome	H Hex Louver
C Gothic Cement		N Satin Nickel	P Prismatic Filter
G7 Beige Gray		1 Shiny Chrome	S Softening Lens
A6 Gray White			
S Warm White			
7 White			

discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI
600mA	CC23-F-600-SP
250mA DW (T)	CC25-DM-250-N
250mA TW (M2)	CC45-D-2x250-N

INTERCHANGEABLE ACCESSORIES





Hole saw
A00832.H0

EXAMPLE CODE COMPOSITION

123456.
OPTICAL FILTER
DECORATIVE RING
CCT
FINISH