

Ariel RF IP55 Wall Washer

Downlights | IP55 | Class III | Dimmable



Fixing
frame



+

Module



LIGHT SOURCE & OPTIC

Power

9W
13W

Lens

Wall washer

Beam Direction

Adjustable:
Tilting +/-25°, rotating +/-360°,
Symmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>90
2400K CRI>90
2700K CRI>90/95
3000K CRI>80/90/95
3500K CRI>90/95
4000K CRI>90

Lifetime

(L70) >77.000 hrs

FIXTURE

Dimensions

Ø 120mm x Hmax 126mm

Material

Aluminium

Body finishes

Warm White (RAL 9010)
White (RAL 9003)
Gray White (RAL 9002)
Gothic Cement (RAL 7033)
Gray (RAL 7012)
Beige Gray (RAL 7006)
Brown (RAL 8019)
Black (RAL 9005)

Weight

450gr

Mounting

Recessed: cut out Ø 86mm

Fixing

Fixing frame for trimless flush mount

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:
500 mA
700mA
Typical Vf= 18V

Driver requirement



Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Ariel RF IP55 Wall Washer

PHOTOMETRIC DATA (3000K CRI>90)


9W - WW UGR 33			13W - WW UGR 34		
					
H (m)	D (m)	Eav (lx)	H (m)	D (m)	Eav (lx)
1	1.55	188	1	1.55	243
2	3.10	47	2	3.10	61
3	4.64	21	3	4.65	27
4	6.19	12	4	6.20	15
5	7.74	8	5	7.75	10
Total lumen output 753 lm			Total lumen output 975 lm		
Efficacy 84 lm/W			Efficacy 75 lm/W		

Ariel RF IP55 Wall Washer

INSTALLATION ACCESSORIES

Fixing rame (A00656.30)


Necessary element: please specify always 1 frame for each Fixture in the purchase order



INSTALLATION TOOL

Hole saw (A00833.H0)


available for easier installation



SUGGESTED REMOTE DRIVERS


On/Off :

CC10-F-500-SI



Ø 28


CC23-F-700-SP



Ø 37


Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC15-D-500-S



Ø 30

CC15-D-700-S



Ø 30

Other options upon request