

Ariel RF IP55



Downlights



IP55

500
700

450 g

Ø86


2

SD
CM

TM
66

Ariel RF IP55 fixing frame

FIXING FRAME	A00656.30
--------------	-----------



Ariel RF IP55 module

[1] 14° Lens not interchangeable

FIXING FRAME



MODULE



500 / 700mA Lumen Output 3000K	9W 500mA - 880 lm	13W 700mA - 1080 lm
14° Lens [1]	7Q4526. _ _ _ _	7Q4527. _ _ _ _
18° Lens	784526. _ _ _ _	784527. _ _ _ _
24° Lens	7G4526. _ _ _ _	7G4527. _ _ _ _
33° Lens	7E4526. _ _ _ _	7E4527. _ _ _ _
52° Lens	754526. _ _ _ _	754527. _ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
○ 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
700mA	CC20-F-700-N	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676



Hole saw
A00833.H0

EXAMPLE CODE COMPOSITION

