

Downlights



IP40

250

500

700

450 g

Ø86


2

2,5

SD CM

TM 66

[2]



Ariel RF fixing frame

FIXING FRAME	A00656.30
--------------	-----------

Ariel RF module

500 / 700mA <small>Lumen Output 3000K</small>	9W <small>500mA - 900 lm</small>	13W <small>700mA - 1100 lm</small>
14° Lens [1]	7Q4425. _ _ _ _	7Q4426. _ _ _ _
18° Lens	784425. _ _ _ _	784426. _ _ _ _
24° Lens	7G4425. _ _ _ _	7G4426. _ _ _ _
33° Lens	7E4425. _ _ _ _	7E4426. _ _ _ _
52° Lens	754425. _ _ _ _	754426. _ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		

Ariel RF dynamic white module

250mA <small>Lumen Output 3000K CRI > 90</small>	9W <small>250mA - 670 lm</small>
33° Lens	7E4949. _ _ _ _
52° Lens	754949. _ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● T DIM TO WARM 1800K / 3000K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● M2 TUNABLE WHITE 1800K / 4000K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray		● 8 Satin Gold	H Hex Louver
● C Gothic Cement		● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray		● 1 Shiny Chrome	S Softening Lens
● A6 Gray White			
● S Warm White			
● 7 White			



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
700mA	CC23-F-700-SP	p. 702
250mA DW (T)	CC25-DM-250-N	
250mA TW (M2)	CC45-D-2x250-N	

INTERCHANGEABLE ACCESSORIES

p. 676

Hole saw
A00833.H0

EXAMPLE CODE COMPOSITION

