








ARMONIA

-  IP40
-  Class III
-  Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
-  Luce continua
Dotless
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  230 gr/m - 200 gr/m
-  Altamente riciclabile
Highly recyclable




Flusso luminoso maggiorato
Ottica media
Luce perfettamente distribuita

Increased luminous flux
Medium beam angle
Perfectly distributed light


ARMONIA OPAL COVER

	12W/m 24Vdc	25W/m 24Vdc	16W/m 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	700lm/m	1300lm/m	750lm/m		
Senza fissaggio Without fixing					
Copertura opalina Opal cover	RTOA1-_____	RTOB1-_____	ANP1-_____ 8	3 Grigio - Gray 4 Nero - Black	U 2200K Q 2500K X 2700K CRI > 90 W 3000K CRI > 90 K 3500K CRI > 90 D 4000K CRI > 90 8 DYNAMIC WHITE
Fissaggio con magneti Magnets fixing					
Copertura opalina Opal cover	RTOA3-_____	RTOB3-_____	ANP2-_____ 8		
Fissaggio con biadesivo Double sided tape fixing					
Copertura opalina Opal cover	RTOA2-_____	RTOB2-_____	ANP3-_____ 8		



ARMONIA LINEAR LENS

	12W/m 24Vdc	25W/m 24Vdc	16W/m 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	950lm/m	1700lm/m	950lm/m		
Senza fissaggio Without fixing					
40° Linear Lens	RTIA1-_____	RTIB1-_____	ANI1-_____ 8	3 Grigio - Gray 4 Nero - Black	U 2200K Q 2500K X 2700K CRI > 90 W 3000K CRI > 90 K 3500K CRI > 90 D 4000K CRI > 90 8 DYNAMIC WHITE
Fissaggio con magneti Magnets fixing					
40° Linear Lens	RTIA3-_____	RTIB3-_____	ANI2-_____ 8		
Fissaggio con biadesivo Double sided tape fixing					
40° Linear Lens	RTIA2-_____	RTIB2-_____	ANI3-_____ 8		



Lunghezze ottimizzate (cm)
Optimized lengths (cm)

005	008	011	014	017	020	023	026	029	032	035	038	041	044	047
050	053	056	059	062	065	068	071	074	077	080	083	086	089	092
095	098	101	104	107	110	113	116	119	122	125	128	131	134	137
140	143	146	149	152	155	158	161	164	167	170	173	176	179	182
185	188	191	194	197	200	203	206	209	212	215	218	221	224	227
230	233	236	239	242	245	248	251	254	257	260	263	266	269	272
275	278	281	284	287	290	293	296	299						

Lunghezze ottimizzate Dynamic White (cm)
Dynamic White optimized lengths (cm)

006	010	014	018	022	026	030	034	038	042	046
050	054	058	062	066	070	074	078	082	086	090
094	098	102	106	110	114	118	122	126	130	134
138	142	146	150	154	158	162	166	170	174	178
182	186	190	194	198	202	206	210	214	218	222
226	230	234	238	242	246	250	254	258	262	266
270	274	278	282	286	290	294	298			

Misure personalizzate su richiesta
Custom lengths upon request


Misure personalizzate su richiesta
Custom lengths upon request

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)


24Vdc
CV70-F-24-N
CV100-L-24-NL
DYNAMIC WHITE

ELEMENTI DI FISSAGGIO
FIXING ELEMENTS


Specifiche tecniche
Technical data



Staffa con vite
Bracket with screw
A00494_0



Staffa magnetica
Magnetic bracket
A00533_0



Clip di fissaggio a molla
Mounting clip
A00705_0

