

LIGHT SOURCE

LED quantity	1
Power max	12 W
Total lumen output (3000K)	12W: 20° - 1311 lm 40° - 941 lm Frosted glass - 819 lm
Efficacy lm/W (3000K)	12W: 20° - 109 lm/W 40° - 78 lm/W Frosted glass - 68 lm/W
CRI	>80
LED Temperature	2700K – 3000K – 4000K
Average operational life	50.000 hours

OPTIC

Material	Aluminum, PMMA
Available optics	20° - 40° - frosted glass
Beam direction	Fixed
Flux symmetry	Symmetrical

FIXTURE

Material	Aluminum, Stainless steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black As per material: 6 - Stainless steel AISI 316L
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

ELECTRICAL FEATURES




Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 350mA
Class	III

MECHANICAL FEATURES

Dimensions	Ø100 x 140 mm
Weight	900 gr
Installation	Wall, floor recessed
Cut-out	Ø92 mm (recessed box A00276.40)
Use	Outdoor

ACCESSORIES

Visors	-
Filters	-
Box/ Frame	Recessed box
Fixing system	-






A00276.40 Recessed box



A00204.30 Recessed box

PHOTOMETRIC DATA

20° Lens – 12W	40° Reflector – 12W	Frosted glass – 12W																																																																																					
																																																																																							
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>20°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.36</td><td>7045</td><td>4509</td></tr> <tr> <td><u>2.00</u></td><td>0.73</td><td>1761</td><td>1127</td></tr> <tr> <td><u>3.00</u></td><td>1.09</td><td>783</td><td>501</td></tr> <tr> <td><u>4.00</u></td><td>1.45</td><td>440</td><td>282</td></tr> <tr> <td><u>5.00</u></td><td>1.82</td><td>282</td><td>180</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	20°				<u>1.00</u>	0.36	7045	4509	<u>2.00</u>	0.73	1761	1127	<u>3.00</u>	1.09	783	501	<u>4.00</u>	1.45	440	282	<u>5.00</u>	1.82	282	180	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>40°</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.62</td><td>1915</td><td>1149</td></tr> <tr> <td><u>2.00</u></td><td>1.23</td><td>479</td><td>287</td></tr> <tr> <td><u>3.00</u></td><td>1.85</td><td>213</td><td>128</td></tr> <tr> <td><u>4.00</u></td><td>2.47</td><td>120</td><td>72</td></tr> <tr> <td><u>5.00</u></td><td>3.08</td><td>77</td><td>46</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	40°				<u>1.00</u>	0.62	1915	1149	<u>2.00</u>	1.23	479	287	<u>3.00</u>	1.85	213	128	<u>4.00</u>	2.47	120	72	<u>5.00</u>	3.08	77	46	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E_{max}(lx)</th><th>E_{av}(lx)</th></tr> <tr> <td>Frost. glass</td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.81</td><td>1003</td><td>563</td></tr> <tr> <td><u>2.00</u></td><td>1.62</td><td>251</td><td>141</td></tr> <tr> <td><u>3.00</u></td><td>2.44</td><td>111</td><td>63</td></tr> <tr> <td><u>4.00</u></td><td>3.25</td><td>63</td><td>35</td></tr> <tr> <td><u>5.00</u></td><td>4.06</td><td>40</td><td>23</td></tr> </table>	H(m)	D(m)	E _{max} (lx)	E _{av} (lx)	Frost. glass				<u>1.00</u>	0.81	1003	563	<u>2.00</u>	1.62	251	141	<u>3.00</u>	2.44	111	63	<u>4.00</u>	3.25	63	35	<u>5.00</u>	4.06	40	23	
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
20°																																																																																							
<u>1.00</u>	0.36	7045	4509																																																																																				
<u>2.00</u>	0.73	1761	1127																																																																																				
<u>3.00</u>	1.09	783	501																																																																																				
<u>4.00</u>	1.45	440	282																																																																																				
<u>5.00</u>	1.82	282	180																																																																																				
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
40°																																																																																							
<u>1.00</u>	0.62	1915	1149																																																																																				
<u>2.00</u>	1.23	479	287																																																																																				
<u>3.00</u>	1.85	213	128																																																																																				
<u>4.00</u>	2.47	120	72																																																																																				
<u>5.00</u>	3.08	77	46																																																																																				
H(m)	D(m)	E _{max} (lx)	E _{av} (lx)																																																																																				
Frost. glass																																																																																							
<u>1.00</u>	0.81	1003	563																																																																																				
<u>2.00</u>	1.62	251	141																																																																																				
<u>3.00</u>	2.44	111	63																																																																																				
<u>4.00</u>	3.25	63	35																																																																																				
<u>5.00</u>	4.06	40	23																																																																																				

NOTES

Provided with 100 cm neoprene cable.