





AURORA 1500 PL

-  IP40
-  Class III
-  Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  600 gr
-  Altamente riciclabile
Highly recyclable



AURORA 1500 PL

	18W 500mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	1500lm	1000lm at source		
 15° Reflector	7A3903._ _		<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black <input type="checkbox"/> W All White	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
 25° Reflector	7G3903._ _			
 40° Reflector	743903._ _	743966._ T DIM-TO-WARM		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-A-350-N
500mA CC20-F-500-N

DIM-TO-WARM

ACCESSORI
ACCESSORIES



Nido D'ape
Hex Louver
A00732.40

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH