

LIGHT SOURCE

| | |
|----------------------------|---|
| LED quantity | 1 |
| Power max | 14 W |
| Total lumen output (3000K) | 713 lm (9°) – 860 lm (40°) |
| Efficacy lm/W (3000K) | 151 lm/W (9°) – 61 lm/W (40°) |
| LOR (3000K) | 45% (9°) - 54% (40°) |
| CRI | >80 - >90 |
| LED Temperature (K) | 2700 K – 3000 K – 3000K CRI>90 – 4000 K |
| Average operational life | 50.000 hours |

OPTIC

| | |
|------------------|---------------------------------------|
| Material | Optical glass |
| Available optics | Zoom optic 9° - 40° |
| Beam direction | Adjustable +/- 90°, rotating +/- 355° |
| Flux symmetry | Symmetrical |
| Accessories | - |

LED FIXTURE

| | |
|---------------------|-----------------------------------|
| Material | Aluminum |
| Finish | Painted (Black, White, All white) |
| Available finishes | Black, White, All white |
| IP Rate | IP40 |
| Working Temperature | -20° ÷ +40° |
| Accessories | - |

ELECTRICAL FEATURES

| | |
|------------------------|--------------------|
| Driver | Remote |
| Dimmable | Push, 1-10V, DALI |
| For emergency lighting | Upon Request |
| Connection in | In series at 450mA |
| Class | III |

MECHANICAL FEATURES

| | |
|-----------------|---------------------------|
| Dimensions (mm) | Ø61 x 140 (cylinder only) |
| Weight | 700 gr |
| Mounting | Wall, ceiling mounting |
| Cut-out (mm) | - |
| Use | Indoor |

NOTES

