



COMETA NGL

- IP40
- Class III
- Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
- Luce continua
Dotless
- Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
- 170 gr/m
- Altamente riciclabile
Highly recyclable




Profilo angolare
Alte prestazioni
Semplicità d'installazione

Angle profile
High performance
Easy installation

COMETA NGL

	12W/m 24Vdc	25W/m 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K Opal cover Transparent cover	500lm/m 900lm/m	900lm/m 1600lm/m		
Senza fissaggio Without fixing			3 Grigio - Gray 4 Nero - Black	U 2200K Q 2500K X 2700K CRI > 90 W 3000K CRI > 90 K 3500K CRI > 90 D 4000K CRI > 90
Copertura opalina Opal cover	Q9FP1-_____-UL	N9FP1-_____-UL		
Copertura trasparente Transparent cover	Q9F21-_____-UL	N9F21-_____-UL		
Fissaggio con magneti Magnets fixing				
Copertura opalina Opal cover	Q5FP1-_____-UL	N5FP1-_____-UL		
Copertura trasparente Transparent cover	Q5F21-_____-UL	N5F21-_____-UL		
Fissaggio con biadesivo Double sided tape fixing				
Copertura opalina Opal cover	Q3FP1-_____-UL	N3FP1-_____-UL		
Copertura trasparente Transparent cover	Q3F21-_____-UL	N3F21-_____-UL		



Lunghezze ottimizzate (cm) Optimized lengths (cm)

004	007	010	013	016	019	022	025	028	031	034	037	040	043	046	049	052	055	058	061	064	067	070	073	076	079
082	085	088	091	094	097	100	103	106	109	112	115	118	121	124	127	130	133	136	139	142	145	148	151	154	157
160	163	166	169	172	175	178	181	184	187	190	193	196	199	202	205	208	211	214	217	220	223	226	229	232	235
238	241	244	247	250	253	256	259	262	265	268	271	274	277	280	283	286	289	292	295	298					

Misure personalizzate su richiesta
Custom lengths upon request




ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)


24Vdc CV100-F-24-NE

ELEMENTI DI FISSAGGIO
FIXING ELEMENTS

Specifiche tecniche
Technical data



Staffa con vite 0°
Bracket with screws 0°
A00784._0



Clip di fissaggio a molla
Mounting clip
A00713._0