

# Continuum IP67 Louver



Linear with Lenses



discover more




# Continuum IP67 Louver



Linear with Lenses



IP67	WIPS	24Vdc	1 m	920 g	2
				1720 g	
				2520 g	
				3320 g	
				4120 g	



## Continuum IP67 Louver


24V	9W	18W	27W	36W	45W
Length	30 cm	60 cm	90 cm	120 cm	150 cm
10° Lens	734395. __	734396. __	734397. __	734398. __	734399. __
25° Lens	764395. __	764396. __	764397. __	764398. __	764399. __
40° Lens	744395. __	744396. __	744397. __	744398. __	744399. __
60° Lens	754395. __	754396. __	754397. __	754398. __	754399. __
Elliptical Lens	774395. __	774396. __	774397. __	774398. __	774399. __

Lumen Output 3000K  
30W/m - 10° Lens: 2500 lm/m

FINISH	CCT
● 4 Black	● U 2200K
	● Y 2700K
	● W 3000K CRI > 90
	● 6 3000K
	● 9 4000K
	● 8 TUNABLE WHITE



IP67	WIPS	230V	1 m	1920 g	2
				2260 g	
				3120 g	
				3980 g	
				4840 g	



## Continuum IP67 Louver 230V

220-240Vac	11W	21W	30W	40W	50W
Length	30 cm	60 cm	90 cm	120 cm	150 cm
10° Lens	734385. __	734386. __	734387. __	734388. __	734389. __
25° Lens	764385. __	764386. __	764387. __	764388. __	764389. __
40° Lens	744385. __	744386. __	744387. __	744388. __	744389. __
60° Lens	754385. __	754386. __	754387. __	754388. __	754389. __
Elliptical Lens	774385. __	774386. __	774387. __	774388. __	774389. __

Lumen Output 3000K  
30W/m - 10° Lens: 2500 lm/m

FINISH	CCT
● 4 Black	● U 2200K
	● Y 2700K
	● W 3000K CRI > 90
	● 6 3000K
	● 9 4000K

## Continuum IP67 louver 230V DALI

220-240Vac	11W	21W	30W	40W	50W
Length	30 cm	60 cm	90 cm	120 cm	150 cm
10° Lens	734390. __	734391. __	734392. __	734393. __	734394. __
25° Lens	764390. __	764391. __	764392. __	764393. __	764394. __
40° Lens	744390. __	744391. __	744392. __	744393. __	744394. __
60° Lens	754390. __	754391. __	754392. __	754393. __	754394. __
Elliptical Lens	774390. __	774391. __	774392. __	774393. __	774394. __

SUGGESTED DRIVERS (not included)

24Vdc CV70-F-24-N p. 292  
24Vdc TW CV100-L-24-NL p. 291

ACCESSORIES

Fixed bracket  
A00949.40

Adjustable bracket  
H30  
A00951.40

Adjustable bracket  
H50  
A00952.40

Adjustable bracket  
H80  
A00953.40

Watertight connector  
24Vdc  
A00357.40

Watertight connector  
220-240Vac  
A01023.40

Fixing plate  
(Only on Request)  
Contact our sales department  
for more information