



IN&OUT m / IN&OUT F

Muovere la luce è un gesto semplice

Changing the light becomes simple








Soluzioni innovative e inaspettate per questo piccolo downlight. La possibilità di estrazione dalla cornice, la rotazione e l'inclinazione ad angolo retto ne fanno un prodotto altamente flessibile e gestibile con semplicità. Ideale per illuminare dettagli architettonici o artistici. Due semplici movimenti e infinite possibilità d'installazione lo rendono uno strumento perfetto per i lighting designer più esigenti.

A small downlight characterized by innovative and surprising solutions. The possibility to take it out from its frame, the rotation and the right angled inclination make this product to be highly flexible and easy to handle. It is ideal for lighting architectural and artistic details up. Two simple movements and infinite possibilities of installation allow it to become a perfect instrument for the more demanding lighting designers.



DGA

IN&OUT m





-  IP40
-  Class III
-  Incasso a parete, soffitto
Wall, ceiling recessed
-  Collegare in serie 500mA o 700mA o 900mA
Connect in series at 500mA or 700mA or 900mA
-  510 gr
-  Ø 72 mm
-  Altamente riciclabile
Highly recyclable




Doppia orientabilità
Installazione a incasso
con molle
Sistema antiabbagliamento

Double adjustability
Installation with springs
Low-glare system





■ IN&OUT m

| | 3W 900mA | 6W 500mA | 9W 700mA | Finiture Finish | Colore LED LED Colour |
|--|-------------|-------------|-------------|--|---|
| Lumen Output 3000K | 250lm | 500lm | 650lm | | |
|  3° Lens | 7T3861._ _ | | | <input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> B Bronzo Scuro Dark Bronze <input type="checkbox"/> H Nero - Black | <input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> J 3500K <input type="checkbox"/> 9 4000K |
|  10° Lens | 733862._ _ | 733863._ _ | | | |
|  30° Lens | 763862._ _ | 763863._ _ | | | |
|  50° Lens | 7D3862._ _ | 7D3863._ _ | | | |



■ IN&OUT m

CON NIDO D'APE - WITH HEX LOUVER

| | 3W 900mA | 6W 500mA | 9W 700mA | Finiture Finish | Colore LED LED Colour |
|--|-------------|-------------|-------------|--|---|
| Lumen Output 3000K | 250lm | 500lm | 650lm | | |
|  3° Lens | 7T3864._ _ | | | <input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> B Bronzo Scuro Dark Bronze <input type="checkbox"/> H Nero - Black | <input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> J 3500K <input type="checkbox"/> 9 4000K |
|  10° Lens | 733865._ _ | 733866._ _ | | | |
|  30° Lens | 763865._ _ | 763866._ _ | | | |
|  50° Lens | 7D3865._ _ | 7D3866._ _ | | | |

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

| | | |
|-------|--------------|----------|
| 500mA | CC20-F-500-N | pag. 590 |
| 700mA | CC20-F-700-N | pag. 598 |
| 900mA | CC20-F-900-N | pag. 602 |

EXAMPLE CODE COMPOSITION

123456.

| |
|------------|
| LED COLOUR |
| FINISH |