






















## IRIDE 3 i IP68

-  IP68
-  Class III
-  Incasso a parete, pavimento  
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 500 cm  
500 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  Collegare in serie 500mA o 1000mA  
Connect in series at 500mA or 1000mA
-  2300 gr
-  Altamente riciclabile  
Highly recyclable



### IRIDE 3 i IP68

	 ALL WHITE 20W 1000mA	 DYNAMIC WHITE 20W 500mA	 RGBW 20W 500mA	Finiture Finish	Colore LED LED Colour
 30° Lens	764120.6 _	764120.68	764120.67	 6 Acciaio Inox Stainless Steel AISI 316L	 Y 2700K  6 3000K  9 4000K  1 5000K  8 DYNAMIC WHITE  7 RGBW
 60° Lens	754120.6 _	754120.68	754120.67		



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

- 500mA **CC52-D-500-NL**  
DYNAMIC WHITE
- CC50-X-500-NL**  
RGBW
- 1000mA **CC52-D-1000-NL**  
ALL WHITE

ACCESSORI  
ACCESSORIES




Controcassa  
Recessed box  
**A00276.40**



Controcassa IP68  
AISI 316L  
IP68 Recessed box  
**A01088.60**



Connettore stagno  
Waterlight connector  
**A00387.40**



EXAMPLE CODE COMPOSITION  
123456.

