


# Lei Solovetro


Steps light | IP40 | Class III | Dimmable





Lei 01



Lei 02



Lei 03



## LIGHT SOURCE & OPTIC

### Power

1W

2W

### Emission

45°

### Beam Direction

Fixed, Asymmetrical

### Material

Methacrylate

### LED quantity

1

### Binning

2 MacAdam Steps

### Color temperature & quality

2200K CRI>80

2700K CRI>80

3000K CRI>80

4000K CRI>80

### Lifetime

(L90) >55.000 hrs

## FIXTURE

### Dimensions

Ø 35mm x H 36mm

### Material

Aluminium

### Body finishes

Black

Gray

White

### Weight

55gr

### Mounting

Recessed

### Fixing

See accessories

### Working temperature

-20° / +40°

## ELECTRICAL FEATURES

### Power supply

Constant current:

350 mA

500 mA

Typical Vf= 3V

### Driver requirement

Remote (not included)

### Control

On/off

Push switch

Phase Cut


0/1-10 V

Casambi

DALI

## PHOTOMETRIC DATA (3000K CRI&gt;80)

## 2W - LEI 01 | UGR 34




H (m)	D (m)	Eav (lx)
1	1.81	6
2	3.62	2
3	5.43	1
4	7.24	0
5	9.05	0

Total lumen output  
32 lm

Efficacy  
16 lm/W

## 2W - LEI 02 | UGR 32




H (m)	D (m)	Eav (lx)
1	0.99	7
2	1.98	2
3	2.97	1
4	3.96	0
5	4.95	0

Total lumen output  
22 lm

Efficacy  
11 lm/W

## 2W - LEI 03 | UGR 30



H (m)	D (m)	Eav (lx)
1	0.99	3
2	1.98	1
3	2.97	0
4	3.96	0
5	4.95	0

Total lumen output  
8 lm

Efficacy  
4 lm/W

INSTALLATION ACCESSORIES

Aluminum recessed box (A01578.40)




Aluminum recessed box with edge (A01581.\_0)



Spring mounting support (A01579.60)




Frame for trimless installation (A01580.30)




INSTALLATION TOOL

Hole saw (A00832.H0)  
available for easier installation




SUGGESTED REMOTE DRIVERS

**On/Off (RIPPLE FREE):**  
CC20-F-350/500-N



**Multifunction (DALI 2, 0/1...10V, PUSH, RIPPLE FREE, AM DIMMING):**  
CC25-DM-350-N



Other options upon request