


Bollards



Micro H500

350mA	3W
Lumen Output 3000K	350mA - 270 lm
15° Lens	7A4330._ _
30° Lens	764330._ _
60° Lens	754330._ _
Frosted Glass	714329._ _
Elliptical Lens	774330._ _


24V	4W
Lumen Output 3000K	24Vdc - 270 lm
15° Lens	7A4734._ _
30° Lens	764734._ _
60° Lens	754734._ _
Frosted Glass	714734._ _
Elliptical Lens	774734._ _

Micro H500 with hex louver

350mA	3W
Lumen Output 3000K	350mA - 190 lm
15° Lens	7A4332._ _
30° Lens	764332._ _
60° Lens	754332._ _
Frosted Glass	714331._ _
Elliptical Lens	774332._ _

24V	4W
Lumen Output 3000K	24Vdc - 190 lm
15° Lens	7A4735._ _
30° Lens	764735._ _
60° Lens	754735._ _
Frosted Glass	714735._ _
Elliptical Lens	774735._ _

FINISH	CCT
4 Black	U 2200K
MF Moka	Y 2700K
4A Anthracite Gray	6 3000K
VB Olive Green	W 3000K CRI > 90
3 Gray	9 4000K



discover more

SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708

ACCESSORIES

35	Ø39
9	
Low glare visor	A00846._0
35	Ø39
35	
Low glare snoot	A00847._0

180	138
57	
Anchor for concrete	A00942.60

Ø55	230
Stainless Steel stake	A00851.60

37	22	36,5
Watertight connector	p. 682	A00387.40

EXAMPLE CODE COMPOSITION

123456.	CCT	FINISH
---------	-----	--------