

## PIEGA IP67




- IP67
- Class II
- Class III
- Montaggio a parete  
Wall mounting
- WIPS - Water Infiltration Protection System
- Cavo in neoprene 100 cm  
100 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
- Collegare in parallelo 24Vdc  
Connect in parallel at 24Vdc
- Alimentazione integrata, collegare alla tensione di rete 220-240Vac  
Built-in driver, connect directly to the line voltage to 220-240Vac
- 110 gr (PIEGA 80 IP67)
- 170 gr (PIEGA 140 IP67)
- Altamente riciclabile  
Highly recyclable




### PIEGA 80 IP67

	2W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	50lm		
Emissione diffusa Diffused emission	7P4018._ _	<ul style="list-style-type: none"> <li>■ 4A Grigio Antracite Anthracite Gray</li> <li>□ 7 Bianco - White</li> <li>■ H Nero - Black</li> <li>■ K Corten - Corten</li> <li>□ L Bianco Perla Oyster White</li> </ul>	<ul style="list-style-type: none"> <li>■ Y 2700K</li> <li>■ 6 3000K</li> <li>■ K 3500K CRI &gt; 90</li> <li>□ D 4000K CRI &gt; 90</li> </ul>



### PIEGA 140 IP67


	4W 24Vdc	4W 220-240Vac	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	100lm	100lm		
Emissione diffusa Diffused emission	7P4022._ _	7P4116._ _	<ul style="list-style-type: none"> <li>■ 4A Grigio Antracite Anthracite Gray</li> <li>□ 7 Bianco - White</li> <li>■ H Nero - Black</li> <li>■ K Corten - Corten</li> <li>□ L Bianco Perla Oyster White</li> </ul>	<ul style="list-style-type: none"> <li>■ Y 2700K</li> <li>■ 6 3000K</li> <li>■ K 3500K CRI &gt; 90</li> <li>□ D 4000K CRI &gt; 90</li> </ul>





ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

24Vdc CV20-F-24-N


ACCESSORI  
ACCESSORIES



Scatola da incasso muratura 502E  
Recessed-box for cement/brickwork 502E  
**A00880.00**



Scatola da incasso muratura 503E  
Recessed-box for cement/brickwork 503E  
**A00882.00**



Micro connettore stagno  
Micro watertight connector  
**A00357.40**

EXAMPLE CODE COMPOSITION  
**123456.**



## PIEGA IP67 m



archiproducts  
DESIGN AWARDS  
WINNER 2020

- IP67
- Class III
- Montaggio a parete  
Wall mounting
- WIPS - Water Infiltration Protection System
- Cavo in neoprene 100 cm  
100 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
- Collegare in parallelo 24Vdc  
Connect in parallel at 24Vdc
- 150 gr (PIEGA 80 IP67 m)
- 210 gr (PIEGA 140 IP67 m)
- 62x48 mm (PIEGA 80 IP67 m)
- 85x48 mm (PIEGA 140 IP67 m)
- Altamente riciclabile  
Highly recyclable




**Design discreto e pulito**  
**Facilità d'installazione**  
**Luce morbida e diffusa**

Refined and discreet design  
Easy to install  
Soft and diffused light


### PIEGA 80 IP67 m

2W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K 50lm		
Emissione diffusa Diffused emission 7P4020._ _	<ul style="list-style-type: none"> <li>4A Grigio Antracite Anthracite Gray</li> <li>7 Bianco - White</li> <li>H Nero - Black</li> <li>K Corten - Corten</li> <li>L Bianco Perla Oyster White</li> </ul>	<ul style="list-style-type: none"> <li>U 2200K</li> <li>Y 2700K</li> <li>6 3000K</li> <li>K 3500K CRI &gt; 90</li> <li>D 4000K CRI &gt; 90</li> </ul>



### PIEGA 140 IP67 m

4W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K 100lm		
Emissione diffusa Diffused emission 7P4024._ _	<ul style="list-style-type: none"> <li>4A Grigio Antracite Anthracite Gray</li> <li>7 Bianco - White</li> <li>H Nero - Black</li> <li>K Corten - Corten</li> <li>L Bianco Perla Oyster White</li> </ul>	<ul style="list-style-type: none"> <li>U 2200K</li> <li>Y 2700K</li> <li>6 3000K</li> <li>K 3500K CRI &gt; 90</li> <li>D 4000K CRI &gt; 90</li> </ul>



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

24Vdc CV20-F-24-N

ACCESSORI  
ACCESSORIES



Micro connettore stagno  
Micro watertight connector  
A00357.40

EXAMPLE CODE COMPOSITION  
123456.

