

Saturno B Multi



Low Voltage Track Projectors



[1] 12° Lens not interchangeable

IP40


48V

370 g

2

2,5

UL LISTED



48Vdc		19W
Lumen Output 3000K		48Vdc - 2100 lm
12° Lens [1]	7Q4815.	_____-UL
18° Lens	784815.	_____-UL
24° Lens	7G4815.	_____-UL
33° Lens	7E4815.	_____-UL
52° Lens	754815.	_____-UL

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER	DIMMING
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter	F ON-OFF
● M8 Brown	● B2 2400K CRI > 90	● 8 Satin Gold	E Elliptical Filter	D DALI
● G3 Gray	● X 2700K CRI > 90	● I Gold Chrome	H Hex Louver	R 1-10V
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter	
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens	
● A6 Gray White	● W 3000K CRI > 90			
● S Warm White	● W1 3000K CRI > 95			
● 7 White	● K 3500K CRI > 90			
	● K1 3500K CRI > 95			
	● D 4000K CRI > 90			



SUGGESTED DRIVERS (not included)

48Vdc CV60-CR-48-NR p. 249

TRACKS ACCESSORIES

Multi track and accessories p. 236

INTERCHANGEABLE ACCESSORIES



p. 235

EXAMPLE CODE COMPOSITION

