



Trium P IP67 230V


Projectors | IP67 | Class II | Not dimmable




Adjustable bracket H30



Adjustable bracket H50



Adjustable bracket H80



Fixing plate

LIGHT SOURCE & OPTIC

Power

8W

Lens

10°

25°

40°

60°

Elliptical Lens

Wall Washer*

Beam Direction

Fixed, Symmetrical

Material

PMMA

LED quantity

3

Binning

2 MacAdam step

Color temperature & quality

2200K CRI>80

2700K CRI>80

3000K CRI>80/90

3500K CRI>80

4000K CRI>80

Lifetime

L80 >60.000 hrs

FIXTURE

Dimensions

137mm x 47mm x H 60mm

Material

Aluminium

Body finishes

Black

Weight

530gr

Mounting

On surface

Fixing

Fixing plate

Adjustable bracket H30

Adjustable bracket H50

Adjustable bracket H80

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Main voltage:

220-240Vac

Driver requirement

Built in

Control

On/off

Feature


Water Infiltration Protection System

*Note: WWOptic cant' be equipped with louvers

Trium P IP67 230V

PHOTOMETRIC DATA (3000K CRI>80)

8W - 10° | UGR 12




H (m)	D (m)	Eav (lx)
1	0.21	5237
2	0.42	1309
3	0.63	582
4	0.84	327
5	1.05	209

Total lumen output
606 lm

Efficacy
78 lm/W

8W - 25° | UGR 13




H (m)	D (m)	Eav (lx)
1	0.52	1516
2	1.03	379
3	1.55	168
4	2.07	95
5	2.59	61

Total lumen output
595 lm

Efficacy
74 lm/W

8W - 40° | UGR 16




H (m)	D (m)	Eav (lx)
1	0.65	715
2	1.31	179
3	1.96	79
4	2.61	45
5	3.27	29

Total lumen output
529 lm

Efficacy
66 lm/W

8W - 60° | UGR 20




H (m)	D (m)	Eav (lx)
1	1.32	263
2	2.64	66
3	3.97	29
4	5.29	16
5	6.61	11

Total lumen output
570lm

Efficacy
71 lm/W

8W - Elliptical Lens | UGR 16




H (m)	D (m)	Eav (lx)
1	0.80-0.12	712
2	1.16-0.25	178
3	2.40-0.37	79
4	3.20-0.49	45
5	4.00-0.61	28

Total lumen output
577 lm

Efficacy
72 lm/W

8W - Wall Washer | UGR 0



H (m)	D (m)	Eav (lx)
1	0.36-4.51	100
2	0.72-9.02	25
3	1.08-13.53	11
4	1.44-18.04	6
5	1.80-22.55	4

Total lumen output
519 lm

Efficacy
65 lm/W


Trium P IP67 230V

ACCESSORIES


Optical Filters

- Louver
- Asy Louver

Low glare visor for T fixing (A01690.40)



Low glare visor for V-Z fixing (A01604.40)



INSTALLATION ACCESSORIES

Watertight connector (A01023.40)

